



# 30-Gallon

## Industrial Two Stage – Gasoline

These air compressor generator combinations are perfect for remodelers, contractors and professionals. With 15.7 CFM and up to 4000 watts, they deliver premium power every time.



AG2-SH13-30ME

### COMPRESSOR PUMP

- Cast iron compressor pump
- Splash lubricated
- Stainless-steel braided discharge hose
- Large canister intake filter
- Oil level sight indicator

### GENERATOR

- Brushless alternator
- Total harmonic distortion (THD) less than 6%
- 100% copper windings
- (2) NEMA 5-20R 120V, 20A and (1) NEMA L6-20R 240V, 20A receptacles

### FRAME

- Powder coated ASME receiver tank
- 3/16-inch base plate to reduce vibration
- Powder coated two-piece belt guard
- Removeable base plate offers flexible installation

### COMPONENTS

- Regulator and two gauges for tank and outlet pressure
- Manual drain valve for proper maintenance
- 16 1/2-inch fly wheel
- Quality pilot valve unloader

### LIMITED WARRANTY

- 3 year engine

### CERTIFICATION

- ASME Boiler and Pressure Vessel Code – UM

| MODEL NUMBER               | CFM @ PSI | CFM @ PSI* | MAX. AC OUTPUT | ALTERNATOR WATTAGE       |                           | DISPLACEMENT/ENGINE                 | DIMENSIONS (LxWxH) | SHIP WT. | NET WT. |
|----------------------------|-----------|------------|----------------|--------------------------|---------------------------|-------------------------------------|--------------------|----------|---------|
|                            |           |            |                | CONT. WITH COMP. ON-LOAD | CONT. WITH COMP. OFF-LOAD |                                     |                    |          |         |
| AG2-SH13-30M               | 16.4 @ 90 | 15.7 @ 175 | 4000 watts     | 2300 watts               | 3500 watts                | 389cc Honda GX390 OHV <sup>+</sup>  | 40x24.5x45in.      | 550 lb.  | 450 lb. |
| AG2-SH13-30ME <sup>^</sup> | 16.4 @ 90 | 15.7 @ 175 | 4000 watts     | 2300 watts               | 3500 watts                | 389cc Honda GX390 OHV <sup>+</sup>  | 40x24.5x45in.      | 557 lb.  | 457 lb. |
| AG2-SK14-30M               | 16.4 @ 90 | 15.7 @ 175 | 4000 watts     | 2300 watts               | 3500 watts                | 429cc Kohler CH440 OHV <sup>+</sup> | 40x24.5x45in.      | 550 lb.  | 450 lb. |
| AG2-SK14-30ME <sup>^</sup> | 16.4 @ 90 | 15.7 @ 175 | 4000 watts     | 2300 watts               | 3500 watts                | 429cc Kohler CH440 OHV <sup>+</sup> | 40x24.5x45in.      | 557 lb.  | 457 lb. |
| AG2-SM14-30M               | 16.4 @ 90 | 15.7 @ 175 | 4000 watts     | 2300 watts               | 3500 watts                | 420cc Mi-T-M OHV                    | 40x24.5x45in.      | 550 lb.  | 450 lb. |
| AG2-SM14-30ME <sup>^</sup> | 16.4 @ 90 | 15.7 @ 175 | 4000 watts     | 2300 watts               | 3500 watts                | 420cc Mi-T-M OHV                    | 40x24.5x45in.      | 557 lb.  | 457 lb. |
| AG2-SV14-30M               | 16.4 @ 90 | 15.7 @ 175 | 4000 watts     | 2300 watts               | 3500 watts                | 408cc Vanguard OHV <sup>+</sup>     | 40x24.5x45in.      | 550 lb.  | 450 lb. |
| AG2-SV14-30ME <sup>^</sup> | 16.4 @ 90 | 15.7 @ 175 | 4000 watts     | 2300 watts               | 3500 watts                | 408cc Vanguard OHV <sup>+</sup>     | 40x24.5x45in.      | 557 lb.  | 457 lb. |

Note: All gasoline models sold in California are required to have a CARB compliant engine. Consult factory.

\*Equipped with 150-PSI maximum rated regulator.

<sup>+</sup>49 state engine. Not for sale in California.

<sup>^</sup>Equipped with electric start – battery, box and cables not included.

# 30-Gallon

## Air Compressor/Generators – Industrial Two Stage – Gasoline

### ACCESSORIES:

| PART NUMBER  | DESCRIPTION   | FITS MODELS |
|--------------|---|-------------|
| 70-0358      | Engine oil drain extension – 14-inch flexible drain hose makes oil changes clean and easy | All models  |
| AW-6000-1002 | Equipment cover – Keeps your equipment clean, dry and looking like new                    | All models  |

### OPTIONS: *Options must be ordered with unit and cannot be added later.*

| PART NUMBER | DESCRIPTION   | FITS MODELS            |
|-------------|---|------------------------|
| AX-0016     | Battery, battery tray, box and 2-foot of cables – Attaches to engine side of unit   | Electric start models  |
| AX-0063     | Lifting hook – For easier portability   | All models             |
| AX-0068     | Idle down – When activated it automatically throttles down engine to conserve fuel  | Honda engine models    |
| AX-0070     | Battery tray, box and 2-foot of cables – Attaches to engine side of unit  | Electric start models  |
| AX-0075     | Idle down – When activated it automatically throttles down engine to conserve fuel  | Mi-T-M engine models   |
| AX-0083     | Idle down – When activated it automatically throttles down engine to conserve fuel  | Vanguard engine models |
| AX-0094     | Remote start/choke, sealed cable – 7-foot wire extension for key switch   | AG2-SH13-30ME          |
| AX-0095     | Remote start/choke, sealed cable – 7-foot wire extension for key switch   | AG2-SM14-30ME          |
| AX-0096     | Remote start/choke, sealed cable – 7-foot wire extension for key switch   | AG2-SV14-30ME          |
| IX-0001     | Vibration isolator pads – Isolators protect the unit from vibration during use. Recommended for models mounted in service truck applications. | All models             |



NEMA 5-20R  
125V



NEMA L6-20R  
240V



**WARNING:** Cancer and Reproductive Harm - [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).