



## Premium Series

Electric – Belt Drive  
Portable

These pressure washers are perfect for cleaning equipment, floors and walls in commercial facilities.



DC-2405-W5E2G

### PUMP

- Belt drive triplex piston pump with ceramic plungers
- External bypass system protects from heat build-up
- Factory preset unloader
- Water filter with clear sleeve for screen inspection

### MOTOR

- Enclosed fan-cooled electric motor
- 10-foot power cord

### FRAME

- Powder coated steel frame
- Totally enclosed belt guard
- 13-inch tires

### COMPONENT

- Heavy-duty dual cogged belt drive system

### UNIT INCLUDES

- Quick connect nozzles – 0°, 15°, 25° and 40°
- 50-foot x 3/8-inch non-marking high pressure hose with quick connects
- Insulated trigger gun

### LIMITED WARRANTY

- 1 year electric motor

MODEL NUMBER	PSI	GPM	HORSEPOWER/MOTOR	PUMP	LANCE	PLUG TYPE	DIMENSIONS (LxWxH)	SHIP WT.	NET WT.
DC-2405-W5E2G	2400	4.6	8.0 HP, 230V, 1Ø, 34.6A	General	36in.	NEMA 6-50P	46x32.5x30in.	405 lb.	322 lb.
DC-2405-W4E3G*	2400	4.6	8.0 HP, 230V, 3Ø, 20.0A or 8.0 HP, 460V, 3Ø, 10.0A	General	36in.	NEMA L15-30P	46x30x30in.	384 lb.	318 lb.
DC-3004-W5E2G	3000	3.9	8.0 HP, 230V, 1Ø, 34.6A	General	36in.	NEMA 6-50P	46x32.5x30in.	405 lb.	322 lb.
DC-3004-W4E3G*	3000	3.9	8.0 HP, 230V, 3Ø, 20.0A or 8.0 HP, 460V, 3Ø, 10.0A	General	36in.	NEMA L15-30P	46x30x30in.	384 lb.	318 lb.
DC-3005-W0E2G	3000	4.8	10.0 HP, 230V, 1Ø, 41.5A	General	36in.	NEMA 6-50P	46x32.5x30in.	470 lb.	396 lb.
DC-3005-W0E3G*	3000	4.8	10.0 HP, 230V, 3Ø, 26.0A or 10.0 HP, 460V, 3Ø, 13.0A	General	36in.	NEMA 15-50P	46x32.5x30in.	450 lb.	376 lb.
DC-4004-W1E3G*	4000	3.9	15.0 HP, 230V, 3Ø, 40.0A or 15.0 HP, 460V, 3Ø, 20.0A	General	48in.	NEMA 15-50P	46x32.5x30in.	505 lb.	431 lb.
DC-5004-W0E3G*	5000	4.0	15.0 HP, 230V, 3Ø, 40.0A or 15.0 HP, 460V, 3Ø, 20.0A	General	48in.	NEMA 15-50P	46x32.5x30in.	505 lb.	431 lb.

\*460V motors available as options.

# Premium Series

## Cold Water – Electric – Belt Drive – Portable

### ACCESSORIES:

PART NUMBER	DESCRIPTION	FITS MODELS
50-0161	High pressure detergent injector – High pressure water mixes with detergent to clean even the heaviest build-up	All models
851-0317	50-foot x 3/4-inch non-marking hose – For when you need extra hose for added mobility	DC-5004-W0E3G
851-0338	50-foot x 3/4-inch non-marking hose – For when you need extra hose for added mobility	2400 to 4000-PSI models
AW-7510-Series	Rotating nozzle – Increase your cleaning power and decrease your cleaning time, 5100-PSI rated	All models
AW-8400-0021	Low pressure detergent injector – Allows the user to apply the recommended detergents	All models

### OPTIONS: *Options must be ordered with unit and cannot be added later.*

PART NUMBER	DESCRIPTION	FITS MODELS
CX-0005	36-inch insulated dual lance – Has high and low pressure tips that allow you to switch to the low pressure detergent injector without having to change tips	2400 to 3000-PSI models
CX-0003	460V on 8.0-HP, 30 models – When 460V of power is available	DC-2405-W4E3G & DC-3004-W4E3G
CX-0062	460V on 10.0-HP, 30 models – When 460V of power is available	DC-3005-W0E3G
CX-0057	460V on 15.0-HP, 30 models – When 460V of power is available	DC-4004-W1E3G & DC-5004-W0E3G
CX-0093	Stationary option – This option will remove the existing tall handle and wheels, which will be replaced with a short handle and rubber feet for stationary applications	DC-2405-W4E3G & DC-3004-W4E3G
CX-0094	Stationary option – This option will remove the existing tall handle and wheels, which will be replaced with a short handle and rubber feet for stationary applications	DC-2405-W5E2G, DC-3004-W5E2G, DC-3005, DC-4004 & DC-5004 models



NEMA 6-50P,  
50-amp plug



NEMA L15-30P,  
30-amp plug



NEMA 15-50P,  
50-amp plug



**WARNING:** Cancer and Reproductive Harm - [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).