



Aluminum Series

Gasoline — Direct Drive
Portable

Known for its strength, portability and patented vibration isolation plate, the aluminum series is a top choice for contractors.



DC-2703-A0H6G

PUMP

- Direct drive triplex piston pump with ceramic plungers
- Stainless-steel and brass trapping unloader
- External bypass system protects from heat build-up

FRAME

- Corrosion-resistant aluminum frame
- Patented vibration isolation plate
- 13-inch tires (10-inch tires on DC-2703 and DC-3003 models)

UNIT INCLUDES

- Quick connect nozzles – 0°, 15°, 25° and 40°
- External downstream detergent injector with detergent nozzle
- 50-foot x 3/8-inch non-marking high pressure hose with quick connects
- Insulated trigger gun

LIMITED WARRANTY

- 3 year engine

CERTIFICATION

- ETL Certified – US (Select models, see chart below)

| MODEL NUMBER | PSI | GPM | DISPLACEMENT/ENGINE | PUMP | LANCE | DIMENSIONS (LxWxH) | SHIP WT. | NET WT. |
|----------------|------|-----|-------------------------|---------|-------|--------------------|----------|---------|
| DC-2703-A0H6G* | 2700 | 2.4 | 196cc Honda GX200 OHV+ | General | 36in. | 39x20.5x24.5in. | 105 lb. | 82 lb. |
| DC-2703-A0K6G* | 2700 | 2.4 | 208cc Kohler CH270 OHV+ | General | 36in. | 39x20.5x24.5in. | 108 lb. | 85 lb. |
| DC-2703-A0H6M* | 2700 | 2.4 | 196cc Honda GX200 OHV+ | Mi-T-M | 36in. | 39x20.5x24.5in. | 97 lb. | 74 lb. |
| DC-2703-A0K6M* | 2700 | 2.4 | 208cc Kohler CH270 OHV+ | Mi-T-M | 36in. | 39x20.5x24.5in. | 106 lb. | 83 lb. |
| DC-2703-A0M6M | 2700 | 2.4 | 212cc Mi-T-M OHV | Mi-T-M | 36in. | 39x20.5x24.5in. | 100 lb. | 73 lb. |
| DC-2703-A0V6M | 2700 | 2.4 | 203cc Vanguard OHV+ | Mi-T-M | 36in. | 39x20.5x24.5in. | 100 lb. | 73 lb. |
| DC-3003-A0H6G* | 3000 | 3.0 | 270cc Honda GX270 OHV+ | General | 36in. | 42.5x23.5x25in. | 160 lb. | 111 lb. |
| DC-3003-A0K6G* | 3000 | 3.0 | 277cc Kohler CH395 OHV+ | General | 36in. | 42.5x23.5x25in. | 170 lb. | 121 lb. |
| DC-3003-A0H6A* | 3000 | 3.0 | 270cc Honda GX270 OHV+ | AR | 36in. | 42.5x23.5x25in. | 148 lb. | 99 lb. |
| DC-3003-A0K6A* | 3000 | 3.0 | 277cc Kohler CH395 OHV+ | AR | 36in. | 42.5x23.5x25in. | 164 lb. | 115 lb. |
| DC-3003-A0M6A | 3000 | 3.0 | 300cc Mi-T-M OHV | AR | 36in. | 42.5x23.5x25in. | 164 lb. | 115 lb. |
| DC-3504-A0H6G* | 3500 | 4.0 | 389cc Honda GX390 OHV+ | General | 48in. | 42.5x23.5x25in. | 175 lb. | 125 lb. |
| DC-3504-A0K6G* | 3500 | 4.0 | 429cc Kohler CH440 OHV+ | General | 48in. | 42.5x23.5x25in. | 180 lb. | 131 lb. |
| DC-3504-A0H6A* | 3500 | 3.5 | 389cc Honda GX390 OHV+ | AR | 48in. | 42.5x23.5x25in. | 175 lb. | 125 lb. |
| DC-3504-A0K6A* | 3500 | 3.5 | 429cc Kohler CH440 OHV+ | AR | 48in. | 42.5x23.5x25in. | 188 lb. | 138 lb. |
| DC-3504-A0M6A | 3500 | 3.5 | 420cc Mi-T-M OHV | AR | 48in. | 42.5x23.5x25in. | 175 lb. | 125 lb. |
| DC-4004-A0H6G* | 4000 | 4.0 | 389cc Honda GX390 OHV+ | General | 48in. | 42.5x23.5x25in. | 177 lb. | 128 lb. |
| DC-4004-A0K6G* | 4000 | 4.0 | 429cc Kohler CH440 OHV+ | General | 48in. | 42.5x23.5x25in. | 185 lb. | 131 lb. |
| DC-4004-A0H6A* | 4000 | 3.5 | 389cc Honda GX390 OHV+ | AR | 48in. | 42.5x23.5x25in. | 168 lb. | 118 lb. |
| DC-4004-A0K6A* | 4000 | 3.5 | 429cc Kohler CH440 OHV+ | AR | 48in. | 42.5x23.5x25in. | 185 lb. | 131 lb. |
| DC-4004-A0M6A | 4000 | 3.5 | 420cc Mi-T-M OHV | AR | 48in. | 42.5x23.5x25in. | 175 lb. | 125 lb. |
| DC-4004-A0V6A | 4000 | 3.5 | 408cc Vanguard OHV+ | AR | 48in. | 42.5x23.5x25in. | 175 lb. | 125 lb. |
| DC-4004-A0H6C* | 4000 | 4.0 | 389cc Honda GX390 OHV+ | CAT | 48in. | 42.5x23.5x25in. | 178 lb. | 128 lb. |

Note: All gasoline models sold in California are required to have a CARB compliant engine. Consult factory.
*49 state engine. Not for sale in California. *ETL Certified – US

Aluminum Series

Cold Water – Gasoline – Direct Drive – Portable

ACCESSORIES:

| PART NUMBER | DESCRIPTION | FITS MODELS |
|----------------|---|-------------|
| 50-0161 | High pressure detergent injector – High pressure water mixes with detergent to clean even the heaviest build-up | All models |
| 851-0338 | 50-foot x 3/4-inch non-marking hose – For when you need extra hose for added mobility | All models |
| AW-7510-Series | Rotating nozzle – Increase your cleaning power and decrease your cleaning time, 5100-PSI rated | All models |
| AW-8400-0021 | Low pressure detergent injector – Allows the user to apply the recommended detergents | All models |

OPTION: *Option must be ordered with unit and cannot be added later.*

| PART NUMBER | DESCRIPTION | FITS MODELS |
|-------------|---|--------------------------|
| CX-0005 | 36-inch insulated dual lance – Has high and low pressure tips that allow you to switch to the low pressure detergent injector without having to change tips | DC-2703 & DC-3003 models |



DC-4004-A0H6G

Made in USA
with Globally Sourced Components



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov