



Premium Series

Gasoline — Belt Drive
Portable

These durable “workhorse” pressure washers are built for blasting away mud, muck, dirt and grime from most any surface.



DC-3004-W4H6G

PUMP

- Belt drive triplex piston pump with ceramic plungers
- External bypass system protects from heat build-up
- Factory preset stainless-steel and brass unloader
- Water filter with clear sleeve for screen inspection

FRAME

- Powder coated steel frame
- Two-piece belt guard
- 13-inch tires

COMPONENT

- Heavy-duty dual cogged belt drive system

UNIT INCLUDES

- Quick connect nozzles – 0°, 15°, 25° and 40°
- 50-foot x 3/8-inch non-marking high pressure hose with quick connects
- Insulated trigger gun

LIMITED WARRANTY

- 3 year engine

CERTIFICATION

- ETL Certified – US (Select models, see chart below)

MODEL NUMBER	PSI	GPM	DISPLACEMENT/ENGINE	PUMP	LANCE	DIMENSIONS (LxWxH)	SHIP WT.	NET WT.
DC-2505-W4H6G*	2500	4.4	389cc Honda GX390 OHV ⁺	General	36in.	45.5x28x26in.	290 lb.	216 lb.
DC-3004-W4H6G*	3000	3.9	389cc Honda GX390 OHV ⁺	General	36in.	45.5x28x26in.	290 lb.	216 lb.
DC-3504-W5H6G*	3500	3.8	389cc Honda GX390 OHV ⁺	General	48in.	46x28x30in.	290 lb.	216 lb.
DC-3504-W5K6G	3500	3.8	429cc Kohler CH440 OHV ⁺	General	48in.	46x28x30in.	290 lb.	216 lb.
DC-3504-W5M6G	3500	3.8	420cc Mi-T-M OHV	General	48in.	46x28x30in.	290 lb.	216 lb.
DC-4004-W5H6G*	4000	3.5	389cc Honda GX390 OHV ⁺	General	48in.	46x28x30in.	290 lb.	216 lb.
DC-4004-W5V6G*	4000	4.0	480cc Vanguard OHV ⁺ with electric start – battery not included	General	48in.	46x28x30in.	330 lb.	256 lb.

Note: All gasoline models sold in California are required to have a CARB compliant engine. Consult factory.

**49 state engine. Not for sale in California. *ETL Certified – US.*

Premium Series

Cold Water – Gasoline – Belt Drive – Portable

ACCESSORIES:

PART NUMBER	DESCRIPTION	FITS MODELS
50-0161	High pressure detergent injector – High pressure water mixes with detergent to clean even the heaviest build-up	All models
851-0338	50-foot x 3/4-inch non-marking hose – High pressure water mixes with detergent to clean even the heaviest build-up	All models
AW-7510-Series	Rotating nozzle – Increase your cleaning power and decrease your cleaning time, 5100-PSI rated	All models
AW-8400-0021	Low pressure detergent injector – Allows the user to apply the recommended detergents	All models

OPTIONS: *Options must be ordered with unit and cannot be added later.*

PART NUMBER	DESCRIPTION	FITS MODELS
CX-0005	36-inch insulated dual lance – Has high and low pressure tips that allow you to switch to the low pressure detergent injector without having to change tips	DC-2505 & DC-3004 models
CX-0054	Roll cage – Designed to protect equipment, comes with a lifting hook, 1/4-inch powder coated steel tubing	All Honda, Kohler and Mi-T-M engine models
CX-0055	Roll cage – Designed to protect equipment, comes with a lifting hook, 1/4-inch powder coated steel tubing	DC-4004-W5V6G
CX-0113	Electric start – battery not included – For easy starting	All Honda engine models



DC-3504-W5H6G



⚠️ WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov.