



Premium Series

Gasoline – Belt Drive
Portable with Roll Cage

This series is ideal for heavy-duty jobs. Equipped with a roll cage, it is great for cleaning ag, construction and industrial equipment.



DC-7004-WC4H6G

PUMP

- Belt drive triplex piston pump with ceramic plungers
- External bypass system protects from heat build-up
- Factory preset stainless-steel and brass unloader
- Water filter with clear sleeve for screen inspection

ENGINE

- Electric start – battery not included

FRAME

- Powder coated steel frame with roll cage and lifting hooks
- Two-piece belt guard
- 13-inch tires with locking tire brake

COMPONENT

- 13-gallon fuel tank capacity for 9½ hour run time

UNIT INCLUDES

- Quick connect nozzles – 0°, 15°, 25° and 40°
- 50-foot x ¾-inch non-marking high pressure hose with quick connects (DC-5000 and DC-6004 models)
- 50-foot x ¾-inch high pressure black hose with quick connects (DC-7004-WC4H6G)
- 50-foot x ½-inch high pressure black hose with quick connects (DC-3008-WC4H6G)
- Insulated trigger gun

LIMITED WARRANTY

- 3 year engine

CERTIFICATION

- ETL Certified – US (Select models, see chart)

MODEL NUMBER	PSI	GPM	DISPLACEMENT/ENGINE	PUMP	LANCE	DIMENSIONS (LxWxH)	SHIP WT.	NET WT.
DC-3008-WC4H6G	3000	8.0	688cc Honda GX630 OHV ⁺	General	48in.	43x27.75x38.5in.	504 lb.	438 lb.
DC-5004-WC4H6A [*]	5000	4.0	688cc Honda GX630 OHV ⁺	AR	48in.	43x27.75x38.5in.	499 lb.	433 lb.
DC-5004-WC4H6G [*]	5000	4.0	688cc Honda GX630 OHV ⁺	General	48in.	43x27.75x38.5in.	515 lb.	449 lb.
DC-5005-WC4H6G [*]	5000	5.0	688cc Honda GX630 OHV ⁺	General	48in.	43x27.75x38.5in.	515 lb.	449 lb.
DC-6004-WC4H6G	6000	3.7	688cc Honda GX630 OHV ⁺	General	48in.	43x27.75x38.5in.	515 lb.	449 lb.
DC-7004-WC4H6G	7000	3.8	688cc Honda GX690 OHV ⁺	General	48in.	43x27.75x38.5in.	515 lb.	449 lb.

Note: All gasoline models sold in California are required to have a CARB compliant engine. Consult factory.

^{*}49 state fuel tank. Not for sale in California. ^{*}ETL Certified – US.

Premium Series

Cold Water – Gasoline – Belt Drive – Portable with Roll Cage

ACCESSORIES:

PART NUMBER	DESCRIPTION	FITS MODELS
851-0089	50-foot x 1/2-inch hose – For when you need extra hose for added mobility	DC-3008-WC4H6G
851-0317	50-foot x 3/4-inch non-marking hose – For when you need extra hose for added mobility	DC-5004, DC-5005 & DC-6004 models
851-0420	50-foot x 3/4-inch hose – For when you need extra hose for added mobility	DC-7004-WC4H6G
AW-7500-0035	Rotating nozzle – Increase your cleaning power and decrease your cleaning time, 0° spray with 25° coverage, 3.5 orifice size	DC-5004 models
AW-7500-0045	Rotating nozzle – Increase your cleaning power and decrease your cleaning time, 0° spray with 25° coverage, 4.5 orifice size	DC-5005-WC4H6G
AW-0018-0374	Rotating nozzle – Increase your cleaning power and decrease your cleaning time, 0° spray with 25° coverage, 3.0 orifice size	DC-6004 & DC-7004 models

OPTION: *Option must be ordered with unit and cannot be added later.*

PART NUMBER	DESCRIPTION	FITS MODELS
CX-0118	Skid feet – Stationary applications	All models



DC-5004-WC4H6A



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov